



### System Features

CPU	Qualcomm APQ8052 Octa core 64-bit Processor
Memory	2GB LPDDR3 RAM 16GB eMMC Flash ROM
OS	Android 6.0/Win 10 IOT Mobile Dual OS
Languages support	English, Simp. Chinese, Traditional Chinese, Japanese, Spanish, German, French

### Display

Gorilla Glass with 5 points multi-touch touch panel  
5.0", Color Full HD, Support finger, wet finger, glove and stylus

### Keypad

6Keys, Scan key left and right, volume key up and down, power key, camera key, function key

### Indicator

2 LED indicate charge/Message  
Vibrator

### Symbologies

<b>2D Imager</b>	
1D	All major codes
2D	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode, Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal Dutch Postal (KIX)

### Audio

Dual speaker  
One receiver and dual noise-cancelling microphones

### Regulatory Approvals

CE, FCC, NCC, BSMI, VCCI, TELEC, CCC, SRRC, RoHS compliance



#### Headquarters

Taipei, Taiwan  
<http://www.ute.com> e-mail: [info@hq.ute.com](mailto:info@hq.ute.com)

#### unitech America

Los Angeles  
<http://us.ute.com> e-mail: [info@us.ute.com](mailto:info@us.ute.com)  
<http://can.ute.com> [info@can.ute.com](mailto:info@can.ute.com)  
Mexico  
<http://latin.ute.com> e-mail: [info@latin.ute.com](mailto:info@latin.ute.com)

#### unitech Asia Pacific & Middle East

Taipei  
<http://apac.ute.com> [info@apac.ute.com](mailto:info@apac.ute.com) / [info@india.ute.com](mailto:info@india.ute.com)  
<http://mideast.ute.com> [info@mideast.ute.com](mailto:info@mideast.ute.com)

### Communication

Camera and Flash Light	5M Pixels Front Camera 16M Pixels Rear Camera CMOS Camera with Auto focus, LED flash light"
External storage	Support MicroSD with SDXC compliance
USB	USB 2.0 OTG
WLAN	IEEE 802.11 a/b/g/n/ac/d/h/i/r
Bluetooth	Bluetooth 4.1 4.1 LE
WWAN	FDD LTE: B1(2100)/B3(1800)/B5(850)/B7(2600)/B8(900)/B20(800) TDD LTE: B38(2600)/B40(2300)/B41(2500) WCDMA: B1(2100)/B5(850)/B8(900) GSM: 900/1800MHz"
GPS	GPS/GLONASS (Only for WAN model)
Other Sensors	Accelerometer, Light sensor, Proximity sensor, Gyroscope, E-compass
NFC	ISO14443-4 (Type A, Type B), ISO15693 Mifare, Felica(ISO/IEC18092)"

### Power Source

Main Battery	Swappable Battery. 3.7V 2960mAh Li-Polymer battery pack (Typical)
Backup Battery capacity	5 min

### Enclosure

Weight	290g with 2D SE4750 Engine version (with Battery)
Dimension	158 X 77 X 16.9 mm

### Software

MoboLink

### Environmental

Operating temperature	-4°F to 122°F (-20°C to 50°C)
Storage temperature	-22°F to 140°F (-30°C to 60°C)
Relative Humidity	10% ~ 90% ( non-condensing )
Drop test to Concrete	1.5 meter MIL-STD 810G
Environmental Sealing	IP67&IP65 Standard
Vibration and Shock test	0.5m tumbles for 300 cycles and 600 drops

### Accessories

Single Slot USB Cradle with Single Slot Battery Charger  
Single Slot Ethernet /USB Client Cradle with Single Slot Battery Charger  
Handstrap  
3.7V 5920mAh Extended Battery(Typical)  
USB Communication Cable  
Power adaptor with universal plugs

#### unitech Europe

Tilburg / Netherlands  
<http://eu.ute.com> e-mail: [info@eu.ute.com](mailto:info@eu.ute.com)

#### unitech Japan

Tokyo  
<http://jp.ute.com> e-mail: [info@jp.ute.com](mailto:info@jp.ute.com)

#### unitech Greater China

Beijing, Shanghai, Guang Zhou, Xiamen  
<http://cn.ute.com> [info@cn.ute.com](mailto:info@cn.ute.com)  
Taipei <http://tw.ute.com> [info@tw.ute.com](mailto:info@tw.ute.com)

