




Using the latest ZK platform and algorithms, iFace800 can hold up to 1,200 face templates and 2,000 fingerprint templates. Supporting multiple authentication methods including face recognition, fingerprint, password, RFID card (and combinations), the iFace800 is ready for integration into the most demanding applications. Communication options include serial/RS485, Ethernet, USB host, and optional Wi-Fi or GPRS. An available 2000 mA battery allows system operation during loss of power events.

Features

- Capacity: 1,200 face templates and 2,000 fingerprint templates
- · Authentication methods: Face, Fingerprint, RFID and/or Password
- Elegant ergonomic design
- · Intuitive touch screen GUI
- Optional built-in backup battery provides approx. 4 hours of continuous operation
- Optional Wi-Fi or GPRS for wireless network connection
- Built-in interfaces for use within access control applications

Installation



Specifications

Display

800 x 480 Pixel, LCD Capacitive Touch Screen High Resolution Infrared Camera

Verification Speed

≤1 sec (typical)

Fingerprint Sensor

ZK Optical

Supported Options

2000 mAh Backup Battery, Prox, Mifare

Camera

Capacity

Face: 1,200(1:N) Fingerprint: 2,000 ID Card: 10,000 Transaction: 100,000

Communications

Data: Ethernet, RS232 / 485, (Optional: Wi-Fi / GPRS) Interface: USB Host, Wiegand Ports Output Only

Power

12V DC at 3A

Environment

Operating Temperature: 32° F - 113° F (0° C - 45° C)

Operating Humidity: 20% - 80%

Dimension

Widht: 7.6 in. (19.3 cm) Hight: 5.5 in. (13.97 cm) Depth: 3.75 in. (9.52 cm) Net Weight: 1.4 lbs. (635 g)

Part Number

iFace 800

What's in the Box













iFace800

Installation Template

Back Plate


Measuring Tape

Network Cable

Diode













Design and Specifications subject to change without notice

201 Circle Drive North, Suite 116 Piscataway, NJ 08854, USA

(1) +1 732-412-6007

1 +1 732-412-6008

sales@zktechnology.com zktechnology.com

