

MCI Keyboard Tech Specs

MCI Keyboards Tech Specs



MCI 3100 with MSR and Glide pad

A) Magnetic Stripe Reader (MSR)

- The MSR is compatible with all magnetic cards according with ISO 7810, ISO 7811, ISO 7812, and ISO 7813
- Bi-directional MSR, cards can be swiped in either direction
- 3 tracks, including the ability to read drivers license format AAMVA and CADL
- Expected Magnetic-head life of 500,000 passes
- Error rate less than 0.5%
- Status LED provides confirmation of a correct read
- Headers and terminators are programmable

B) Touchpad

A touchpad could be installed in a 3 x 4 key position at the upper left or right corner. In case of the MCI3000, the touchpad option is installed at the arrow keys section. Only available when using USB interface

- Fully compatible with Windows 98, NT 4.0, 2000, XP and Linux native drivers.
- IP 54
- Capacitive-sensing technology
- No additional drivers are necessary, works as a mouse



Customized MCI 128 with SCR, MSR and Keylock

C) Keylock

- 5 position
- Headers and terminators are programmable
- IP-54 rating for dust and liquid protection
- Lifetime: 20,000 cycles

D) Smart Card Reader (SCR)

- Current consumption of 60mA
- USB Interface
- Application Interface PC/SC, OCF and CT-API
- ISO 7816 and EMV 2000 compatible
- CAC compatible
- Microsoft WHQL certified

Available options per keyboard model

	MSR	Keylock	Smart Card	Touchpad	Alpha layout
MCI 3100	•	•	•	•	• **
MCI 128	•	•	•	•	•
MCI 96	•	•	•	•	•
MCI 84	•	•	N/A	• *	N/A
MCI 60	•	•	N/A	• *	N/A
MSI 60	•	•	N/A	• *	N/A
MCI 30	•	N/A	N/A	N/A	N/A

* Special order

** MCI 3100 only available in Alphanumeric version

MCI Keyboard Tech Specs



MCI 128 with MSR

Keys and Keypad

- Life Span > 30 Million Cycles
- Multilayer patented technology provides IP54 protection against dust and spills
- Keys available in Black and White.
Additional colors on request, minimal order quantities apply
- Customized keys available
- Key spacing 19 mm
- Actuation travel 3.5 mm
- Actuation Force 0.6 N
- Impact stability 10 N, 1 min
- Bounce Time 5 ms max.
- Contact Resistance 800 ohm max.

Electronics

Supply Voltage	+ 5 V \pm 5%
Current consumption	Max 60 mA
Interface	USB (PS/2 adaptor included). Hard-wired PS/2 interface available upon request. Minimum order quantities apply.
Auto repeat	All keys, repeat frequency and delay time are programmable.
4 Status LEDS	<ul style="list-style-type: none">• Caps Lock• Scroll Lock• Num Lock• MSR status
Tone Indicator	Accessible via OPOS

Temperature and Environment Ratings

Operational Temperature	0° C to 50° C
Air Pressure	700 hPa to 1060 hPa
Relative Humidity	5% to 93%
Storage & Transportation	-40°C to 60°C
Climatic class	DIN-IEC 68, part 1, appendix A

Materials

Housing	ABS
Guide Frame	Polystrol
Switching Membrane	Polyester
Spring Elements	Elastomer
Textile filter	Trevira
Keys and Keycaps	PBT/POM/PC

Certifications

ESD/EMC/EMV	CE Approval
Emissions	<ul style="list-style-type: none">• EN55022• FCC Subpart 15, Class A
Interface Immunity	<ul style="list-style-type: none">• Electrostatic discharge immunity according to EN 50082-1, resistance limit 8 kV (air discharge).• Radiated, radio-frequency electromagnetic field immunity, severity of test 3 V/m.

Drivers and Tools

- OPOS and JavaPOS drivers for MSR, Keylock, Keyboard and Tone Indicator. JavaPOS driver available for Windows and Linux
- Programming tools for Windows and DOS.
- 128 programmable levels.
- User interface
- Remote programming tools (Network)
- WEPOS verified

PrehKeyTec

www.prehkeytecusa.com