

PA700V: Anytime, Anywhere

Deliver the connectivity your customers crave. This stylish device is always connected to the heart of their business. Unites the intuitive power of 4G Android with the rugged efficiency of enterprise computing.

Android Power

Android 4.3 is widely used and simple to develop on. Runs sophisticated enterprise-level apps alongside popular consumer-grade tools.

Rugged

The PAZOOV performs reliably in extreme temperatures, withstands extensive vibrations, and is sealed against water and dust. The beautiful Gorilla Glass screen can take multiple 4-foot drops face-first and resists scratches.

Large Vibrant Display

With 4.7" of screen real estate, the PA700V supports information intensive applications. The fully illuminated and sunlight readable screen facilitates outdoor applications.

Verizon Certified

4G certification has arrived. Give your customers access to data on the nation's largest 4G network. Now they can use rugged Android to stay connected to their business.

Main Features:

- Verizon 4G LTE
- 4.7" Gorilla Glass Touchscreen
- Integrated 2D barcode scanner
- Bluetooth 4.0/WiFi/GPS
- IP65 and Military Grade 810G
- Android 4.3





unitech

PA700V Specifications

Wetmory T CB RAW Extended battery T how OS Android 4.3 Extended battery T how Supported Languages English, Simp. Chinese, Traditional Chinese, Japanese, Spanish, German, French Audio TW Speaker 85 dB at 10cm, 3.5mm Audio Jack, Receiver, Microphone Display Gorilla Glass 2 with S-point Capacitive Touch Parel 4.7" Color ICD 720x1280 High Resolution Display Enclosure TW Speaker 85 dB at 10cm, 3.5mm Audio Jack, Receiver, Microphone Keypad 4 Function Keys, dual scanning triggers Enclosure Weight 10 oz (with battery) Indicator LED indicator //Vibrator Environmental Operating temperature Storage	System CPU	1.5 Ghz TI OMAP 4470	Power Source Main battery	
OS Supported Languages Android 4.3 English, Simp. Chinese, Traditional Chinese, Japanese, Spanish, German, French Audio TWS speaker 85 dB at 10cm, 3.5mm Audio Jack, Receiver, Microphone Display Corilla Glass 2 with 5-point Capacitive Touch Panel 4.7* Color ICD 720x1280 High Resolution Display Enclosure Keypad 4 Function Keys, dual scanning triggers Enclosure Indicator LED indicator /Vibrator Environmental Operating temperature Relative humidity Drop roting 14 ^{ep} to 122 ^{ep} 4 feet Symbologies 2D Imager PDF417, MicroPDF417, Compasite, RSS, TIC-39, Datamatrix, GR Code, Micro GR Code, Aztec, Max/Code, Postal Codes: US PostAl, Japan Postal Dutch Postal (KIX) Regulatory Approvals CF, NCC, FCC, BSWI, VCCI, CCC, RoHS Communication Camera and Flash Light Bluetooth Herbooth UterBands 4, 13 (1720/2100 AWS, 700) ITE Cot.1, DL/UL max: 10.3Mbps / 5.2, Mbps Strate 13 (1720/2100 AWS, 700) ITE Cot.1, DL/UL max: 10.3Mbps / 5.2, Mbps VNAN LEEE 802.11 b/g/n	Memory		1	Rechargable 3.7V 3220mAh Lithium Polymer
Supported Languages English, Simp. Chinese, Traditional Chinese, Japanese, Spanish, German, French Audio IWV Speaker 85 dB at 10cm, 3.5mm Audio Jack, Receiver, Microphone Display Gorilla Class 2 with 5-point Capacitive Touch Panel 4.7" Color ICD 720x1280 High Resolution Display Enclosure Veight 10 oz (with battery) Keypad 4 Function Keys, dual scanning triggers Enclosure 0.3" x 3.1" x 0.7" Indicator LED indicator //Vibrator Operating temperature Storage temperature Relative humidity 14 ^a F to 122 ^a F Symbologies 20 Imager PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, GR Code, Micro QR Code, Aztec, MaxiCode, Postal Codes: US Postol, Austrolinon Postal Japan Postal Utch Postal (KIX) Postal, LS Poner, UK Postal, Austrolinon Postal Japan Postal Codes: US Postal, Austrolinon Postal Japan Postal Codes: US Postal, Austrolinon Postal Japan Postal KIX) Communication S MP camera with flash Bluetooth 4.0 Bluetooth 4.0 Interface US 2.0 VWAN EFE 80.21 Ib /g/n WIAN LEE 80.21 Ib /g/n S MP camera with flash	\cap s		Extended battery	1 hour
Indicator Japanese, Spanish, German, French Audio 1W Speaker 85 dB at 10cm, 3.5mm Audio Display Gorilla Glass 2 with 5-point Capacitive Touch Penel 4.7" Color LCD 720x1280 High Resolution Display Enclosure Keypad 4 Function Keys, dual scanning triggers Enclosure Indicator LED indicator /Vibrator Dimensions 6.3" x 3.1" x 0.7" Symbologies Diff. The composite RSS, TIC-39, Datametrix, QR Code, Micro QR Code, Azte, MaxCode, Wicro QR Code, Azte, MaxCode, Wicro QR Code, Azte, MaxCode, Micro QR Code, Azte, MaxCode, Store Postal Codes: US PostNet, US Planet, UK Postal (KIX) Prostal Dutch Postal (KIX) Regulatory Approvals CE, NCC, FCC, BSMI, VCCI, CCC, RoHS compliance Communication Camera and Flash light Bluetooth 5 MP camera with flash Bluetooth 4.1 St (1200 // 2100 AWS, 700) LTE Fabrids 4.1 St (1700 // 2100 AWS, 700) LTE Cant.), DL/UL max: 10.3Mbps / 5.2 Mbps				
Panel 4.7" Color LCD 720x1280 High Resolution Display Enclosure Weight 10 oz (with battery) Keypad 4 Function Keys, dual scanning triggers Dimensions 6.3" x 3.1" x 0.7" Indicator LED indicator /Vibrator Environmental Operating temperature Storage temperature Storage temperature 20 Imager 14% to 122% Symbologies 2D Imager PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR Code, Micro QR Code, Aztec, MaxiCode, Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal Dutch Postal (KIX) Regulatory Approvals CE, NCC, FCC, BSMI, VCCI, CCC, RoHS compliance Communication Gamera and Flash Ught Bluetooth 5 MP camera with flash Bluetooth 4.0 S MP camera with flash Bluetooth 4.0 Bluetooth 4.0 Interface USB 2.0 USB 2.0 VWAN AG ITE Verizon Carified ITE (PDD) 3GPP Rel. 9+ ITE-8ands 4, 13 (17/20/2100 AWS, 700) ITE Cands 4, 13 (17			Audio	
Keypad 4 Function Keys, dual scanning triggers Indicator LED indicator /Vibrator Environmental Operating temperature 14°F to 122°F 5 torage temperature -4°F to 140°F 6 to 140°F Symbologies PDF417, MicroPDF417, Composite, RSS, TLC:39, Datamatrix, QR Code, Micro QR Code, Aztec, MaxiCode, Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal Dutch Postal (KIX) IP65 Communication CE, NCC, FCC, BSMI, VCCI, CCC, RoHS compliance Regulatory Approvals CE, NCC, FCC, BSMI, VCCI, CCC, RoHS compliance Current and Flash Light 5 MP camera with flash Bluetooth Bluetooth 4.0 Bluetooth 4.0 Regulatory Approvals CE, NCC, FCC, BSMI, VCCI, CCC, RoHS compliance WVWAN 4G ITE Verizon Certified ITE (FID) 3GPP Rel. 9+ ITEBands 4, 13 (1700/2100 AVVS, 700) ITE Cat. 1, DL/UL max: 10.3Mbps / 5.2 Mbps VUAN IEEE 802.11 b/g/n	Display	Panel 4.7" Color LCD 720x1280 High	Weight	. ,,
Indicator LED indicator /Vibrator Operating temperature 14°F to 122°F Symbologies -4°F to 140°F 2D Imager PDF417, MicroPDF417, Composite, RSS, TIC-39, Datamatrix, QR Code, Micro QR Code, Aztec, MaxiCode, Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal Dutch Postal (KIX) PME Communication Camera and Flash Light 5 MP camera with flash Bluetooth Bluetooth 4.0 Interface USB 2.0 WWAN USB 2.0 WUAN IEEE 802.11 b/g/n	Keypad	4 Function Keys, dual scanning triggers	Dimensions	6.3" × 3.1" × 0.7"
Symbologies 2D Imager PDF417, MicroPDF417, Composite, RSS, TIC-39, Datamatrix, QR Code, Micro QR Code, Aztec, MaxiCode, Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal Dutch Postal (KIX) Storage temperature IP65 -4°F to 140°F Relative humidity Communication Camera and Flash Light 5 MP camera with flash Bluetooth IIIC-39, Datamatrix, QR Code, Micro QR Codes: US PostNet, US Planet, UK Postal, Australian Postal Dutch Postal (KIX) Regulatory Approvals CE, NCC, FCC, BSMI, VCCI, CCC, RoHS compliance Communication 5 MP camera with flash Bluetooth 4.0 Environmental seal IIIC-39, Datamatrix, QR Code, Micro QR Codes: US PostNet, US Planet, UK Postal, Australian Postal Dutch Postal (KIX) CE, NCC, FCC, BSMI, VCCI, CCC, RoHS compliance VWWAN 4 G ITE Verizon Certified LTE (FDD) 3GPP Rel. 9+ LTE-Bands 4, 13 (1700/2100 AWS, 700) LTE Cat.1, DL/UL max: 10.3Mbps / 5.2 Mbps Yutan IEEE 802.111 b/g/n			Environmental	
Symbologies 2D Imager PDF417, MicroPDF417, Composite, RSS, TLC:39, Datamatrix, QR Code, Micro QR Code, Aztec, MaxiCode, Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal Dutch Postal (KIX) Vibration and Shock test MIL-STD-810F, 514.4 Process II Communication Regulatory Approvals CE, NCC, FCC, BSMI, VCCI, CCC, RoHS compliance Camera and Flash Light 5 MP camera with flash Bluetooth 4.0 Interface USB 2.0 WWVAN 4G ITE Verizon Certified ITE (FDD) 3GPP Rel. 9+ ITE-Bands 4, 13 (1700/2100 AWS, 700) ITE Cat.1, DL/UL max: 10.3Mbps / 5.2 Mbps WLAN IEEE 802.11 b/g/n	Indicator	LED indicator /Vibrator	Storage temperature Relative humidity Drop rating	-4°F to 140°F 5% ~ 95% (Non-Condensing) 4 feet
Communication Structure Compliance Camera and Flash Light 5 MP camera with flash Bluetooth Bluetooth 4.0 Interface USB 2.0 VWWAN 4G ITE Verizon Certified ITE (FDD) 3GPP Rel. 9+ ITE-Bands 4, 13 (1700/2100 AWS, 700) ITE Cat.1, DL/UL max: 10.3Mbps / 5.2 Mbps WLAN IEEE 802.11 b/g/n		TLC-39, Datamatrix, QR Code, Micro QR Code, Aztec, MaxiCode, Postal Codes: US		
Camera and Flash Light 5 MP camera with flash Bluetooth Bluetooth 4.0 Interface USB 2.0 VVVAN 4G LTE Verizon Certified LTE (FDD) 3GPP Rel. 9+ LTE-Bands 4, 13 (1700/2100 AWS, 700) LTE Cat.1, DL/UL max: 10.3Mbps / 5.2 Mbps WLAN IEEE 802.11 b/g/n		Postal, Japan Postal Dutch Postal (KIX)	Regulatory Approvals	
Bluetooth Bluetooth 4.0 Interface USB 2.0 VVVAN 4G LTE Verizon Certified LTE (FDD) 3GPP Rel. 9+ LTE-Bands 4, 13 (1700/2100 AWS, 700) LTE Cat.1, DL/UL max: 10.3Mbps / 5.2 Mbps WLAN IEEE 802.11 b/g/n		5 MP camera with flash		
WWAN 4G LTE Verizon Certified LTE (FDD) 3GPP Rel. 9+ LTE-Bands 4, 13 (1700/2100 AWS, 700) LTE Cat.1, DL/UL max: 10.3Mbps / 5.2 Mbps WLAN IEEE 802.11 b/g/n	0			
LTE (FDD) 3GPP Rel. 9+ LTE-Bands 4, 13 (1700/2100 AWS, 700) LTE Cat.1, DL/UL max: 10.3Mbps / 5.2 Mbps WLAN IEEE 802.11 b/g/n	Interface	USB 2.0		
	WWAN	LTE (FDD) 3GPP Rel. 9+ LTE-Bands 4, 13 (1700/2100 AWS, 700) LTE Cat.1, DL/UL max: 10.3Mbps / 5.2		
	WLAN	IEEE 802.11 b/g/n		

TARGET MARKETS & APPLICATIONS		
Direct Store Delivery	Inventory Management Order Automation Delivery	Stock and sell smarter with automatic updates to the back-end system.
Logistics and Transportation	Proof-of-Delivery Asset Tracking Scheduling	Update service reports remotely or request assistance.
Field Service	Asset Management Parts Inventory Digital Invoices	Field force automation for on-the-go data collection and real-time updates.



GPS

Specifications subject to change without notice.

Copyright 2016 Unitech Electronics Co., Ltd. All rights reserved. Unitech is a registered trademark of Unitech Electronics Co., Ltd.

Yes

All product and company names are trademarks, service marks, or registered trademarks of their respective owners.



www.unitechbarcode.com Unitech America | info@us.ute.com | (800) 861. 8643